



KENT C CITY

TECHNICAL DATA SHEET – COUNTRY NAME

DIMENSIONS

Length	(mm)	12000
Width	(mm)	2540
Height	(mm)	3145
Wheelbase	(mm)	5900
Front Track Width	(mm)	2151
Rear Track Width	(mm)	1874
Front Overhang	(mm)	2700
Rear Overhang	(mm)	3400
Interior Height	(mm)	2215-2415

WEIGHTS

Axle Capacity (Front)	(kg)	6500
Axle Capacity (Rear)	(kg)	11500
Gross Vehicle Weight	(kg)	17955

PASSENGER CAPACITY

Standard Seat Layout	29+65+1
Seat Layout Options	29+60+1wch+1

TECHNICAL SPECIFICATIONS

Engine

Manufacturer / Type	Cummins ISB6.7E6280B
Number of Cylinders	6
Engine Volume	6700 cc
Max. Power	204 kW (280 HP) / 2100 d.d.
Max. Torque	1100 Nm / 1200 d.d.
Engine Location	Rear

Transmission	Automatic Transmission (VOITH)
	4 Forward, 1 Reverse

Suspension

Front	2 air bellows, 2 hydraulic shock absorbers, 1 levelling sensor
Rear	4 air bellows, 4 hydraulic shock absorbers, 2 levelling sensors

TECHNICAL SPECIFICATIONS

Differential

Manufacturer	ZF
Diff. Ratio	6.2

Brakes

Front and Rear	Full-air self adjusting, dual circuit disc brakes
----------------	---

Steering System

Hydraulic

Doors

Front	Double flaps inward swinging
Middle	Double flaps inward swinging
Rear	Double flaps inward swinging

Electrical System

Batteries	2 x 12V 225 Ah
Alternator	2 x 120A

Tyres

275/70 R22,5

Double tyres at rear

Gradeability

(%) 30

Fuel Tank Capacity

(lt) 300

Ad-blue tank capacity

(lt) 50

Turning Radius

Wall to Wall (mm) 10200

Body

Monocoque



STANDARD AND OPTIONAL EQUIPMENTS

POWERTRAIN

ABS, ASR, EBS	S
ECAS III	S
Kneeling	S
Automatic engine oil fill-up system	S
Automatic chassis lubrication (ACL)	S

AC

A/C (39kW)	S
Additional heater	S
Two rear heaters	S
Front box	S

WINDOWS

Single glazed side windows	S
Heated front door window	S
Heated driver's window	S
Heated windscreen	S
Heat resistance for front screen	S
Double glazed side windows	O

ACCESSIBILITY

Exterior handicapped button	S
Wheelchair area	S
Four priority seats	S
Handicapped ramp	S
Maternal-child seat	S
Stainless steel holding bars	S

SEATING

Non-reclining passenger seats	S
Air assisted driver's seat with seatbelt and armrest	S

SAFETY

DRL	S
Heated & digital controllable coach type (horn) rear view mirror	S
Driver cabin door with transparent panel	S
Fire extinguishers	S
First aid kit	S
STOP buttons with Braille alphabet	S

Illuminated door buttons	S
LED interior lighting	S
Safety system for doors	S
Fire alert and extinguishing system for engine compartment	S
Reverse gear buzzer	S
Rear park sensors	S
Manual circuit breaker near batteries	S
Surveillance cameras at middle and rear doors	S
Rear view camera and 7" monitor	S

PASSENGER INFO

Digital signboards at front, rear and side	S
Announcement system both inside and outside	S
Microphone	S
2x25W Amplificator	S
6 speakers (inside)	S
Speaker (outside)	S

DRIVER COMFORT

Adjustable steering column	S
Electrically controlled sunvisor	S
Manual sunvisor at driver side	S
Locker	S
Coat Hanger	S

BODY

Fog lamps (front and rear)	S
Bus stop system	S
High riding	S
Metallic Colour	O

OTHER FEATURES

Battery main switch	S
Digital tachograph	S
Fuel consumption indicator	S
Roof hatches	S

*Otokar Otomotiv ve Savunma Sanayii A.Ş reserves the right to make changes in the specifications and the design of the products without prior notice. Some data may refer nominal values. Images shown may have been prepared for generic use and some of the information and/or accessories which are not available in some countries or which, in order to satisfy local market demand or regulatory controls in such countries, may only be available in different specifications or configurations.